

# THIN-CRETE VERTICAL

## STAMPABLE OVERLAY FOR VERTICAL APPLICATION

### DESCRIPTION

**Increte Systems' Thin-Crete Vertical** mix is an easy to use, polymer-modified, cementitious, one-component surfacing compound designed for vertical stamping. Thin-Crete Vertical is lightweight, easy to trowel and can be built to a thickness of over 2 inches.

### FEATURES

- Simple mix...Just add water
- Light weight
- Clings to vertical surfaces
- Builds up to 2 inches in a single application
- Can be applied over:
  - Cinder block
  - Backer board
  - Gypsum
  - Wood
  - Insulated Concrete Forms
- Interior or exterior
- Contains no asbestos
- Easy to use and safe.
- Low water demand
- Long term durability.
- Insulating properties

### PACKAGING

40 lbs units

### SHELF LIFE

2 years with proper storage conditions

### COVERAGE

Each 40 lb. Bag covers approximately 16 square feet at ½ inch thickness or 8 square feet at 1 inch.



Decorative Concrete  
Technology

#### INCRETE SYSTEMS

1611 Gunn Hwy. Odessa, FL 33556

Phone: 813-886-8811 - Toll-Free: 800-752-4626 - Fax: 813-920-1516

[www.increte.com](http://www.increte.com)

A Division of The Euclid Chemical Company An **RPM** Company

# THIN-CRETE VERTICAL

## STAMPABLE CEMENTITIOUS OVERLAY FOR WALLS

### DIRECTIONS FOR USE

#### **SURFACE PREPARATION**

Surfaces must be clean and free from any coatings or sealers. Use a wire or plastic mesh or lathe if movement is possible or if applied over wood. When applying over sheets of backer board, gypsum or sheet rock, use mesh at seams.

**Step 1: Prime with Bond-Crete.** Two coats may be required on porous surfaces. Allow to set until clear but still tacky. Do not exceed 24 hours between application of Bond-Crete and scratch coat.

**Step 2: Apply a Scratch Coat.** The scratch coat will provide a rough surface for the stamp coat to cling and prevent sagging and sliding. Mix 4 to 5 quarts of cool water with one 40-pound bag of THIN-CRETE VERTICAL. Mix for 2–3 minutes and adjust the water as needed. Apply a very thin coat with trowel. Increte SPRAY DECK GROUT may also be used for a scratch coat.

**Step 3: Apply the Stamp Coat.** Once the scratch coat has set, mix and apply the stamp coat. Add one 40-pound bag of THIN-CRETE VERTICAL to 4 quarts of cool water and mix for 2-3 minutes. Additional water can be added, but will reduce your ability to build thickness without sagging or sliding. Increte Cement Retarder may be used to increase working time.

**Step 4: Stamp.** When the material reaches a spongy state, and before the surface begins to form a crust it is time to stamp. This may be immediately after the stamp coat has been applied or up to three hours later depending on thickness and weather conditions. Use Increte Liquid Release on stamping tools and on the surface to be stamped. Grout lines and squeeze marks are best cleaned up the next day. Surface may also be sculpted, molded or carved manually.

**Step 5: Color.** There are a variety of coloring options including integrally coloring with Thin-Crete Color Packs or topical colorants such as Stain-Crete, Thin-Crete Antiquing Agent, Increte Stone Essence, or Increte Stain Sealers.

### COLORS

Available in standard gray and light gray.

### PRECAUTIONS/LIMITATIONS

**CAUTION** – Do not take internally. If swallowed contact a physician immediately.  
**KEEP AWAY FROM CHILDREN.**  
Always consult MSDS prior to use.

**WARRANTY** All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

**IMPORTANT NOTICE:** THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANT ABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED, THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.